



# CL

## Modular Clarifiers Capable of Pre-Treatment, Sewer Discharge or Recycling of Wash-Water

Flow Rates of up to 30 GPM | Compact Footprint | Self-Contained Yet Modular Flexibility | Above Ground Design



■ **CL-603 with Filter Pac III**  
Recycle System



■ **CL-304 Extra-Compact**  
Recycle System



■ **CL-600 Discharge**  
System



■ **CL-30 Pre-Treatment**  
Solids Separator

### WHY THE CL IS AMERICA'S MOST VERSATILE WATER TREATMENT SYSTEM

No other wash-water treatment system is as versatile and modular as the Water Maze CL.

The four models can stand alone or, in some cases, be matched with a Filter Pac module to serve as a solids separator, a treat-and-discharge unit or even a recycle system.

- The CL-603 is a full recycling system when matched with the modular Filter Pac III.

- The CL-304 serves as an extra-compact and affordable recycling system engineered to fit on a single platform.

- The CL-600 discharges to the sanitary sewer.

- The CL-30 is ideal as a solids separator in pre-treatment.

The Water Maze Filter Pac III offers additional filtration for meeting the environmental and water conservation needs of most wash-water applications.

**NOTE:** We are constantly improving and updating our products. Consequently, pictures, features and specifications in this brochure may differ slightly from current models. Water Maze is not responsible for procurement of regulatory, operation and/or discharge permits that may be required by city, county, state or federal agencies for particular uses of the Water Maze product line. The customer is responsible for procuring any hazardous or non-hazardous regulatory, operating and/or discharge permits for complying with codes or other governmental requirements associated with the installation, use, or disposal of waste associated with the Water Maze product line.

CL Specifications	RECYCLE*	RECYCLE	DISCHARGE	SOLIDS SEPARATOR
MODEL	CL-603A	CL-304A	CL-600D	CL-30A
Maximum Flow Rate	1 - 30 GPM	1 - 5 GPM	1 - 30 GPM	1 - 30 GPM
Oil/Water Separator Cap.	600 gal.	300 gal.	600 gal.	600 gal.
Electrical Configuration	230V 1ph 22A	230V 1ph 15A	120V 1ph 20A	230V 1ph 4.6A
Solids Separator Chamber	yes	yes	yes	yes
Sanitizing Method	Ozone, Series 400	Chlorination	Ozone, Series 400	N/A
Coalescing Pack	490 sq.ft.	94 sq.ft.	490 sq.ft.	90 sq.ft.
Holding Tanks	65 gal.	40 gal.	N/A	165 gal. (Clarified)
Dimensions (L x W x H)	60" x 83" x 106"	72" x 72" x 90"	60" x 83" x 106"	60" x 83" x 106"
Net Dry Weight (approx)	975 lbs.	1545 lbs.	835 lbs.	825 lbs.

\* Must add Filter Pac III in order to recycle wash water with this model

Filter Pac III Specs	Pac III - 30-778
MODEL	Pac III - 30-778
Maximum Flow Rate	30 GPM
Electrical Config	D/A 120/230V 1ph 21.0/10.5A
Media Filter	330 lbs.
Filter Pump	1.5 HP
Cartridge Filter	500 sq.ft. 300
Carbon Filter	lbs.
Dimensions (LxWxH)	61" x 61" x 46"
Ship Weight (approx)	990 lbs.

**OPTIONS INCLUDE:** Auto Purge system that automatically removes solids from cone-bottom tank (not applicable to CL-30); advanced digital ORP/pH Controller for optimum wash-water management; corona discharge Ozone Generator

See your Water Maze Dealer for part numbers and pricing.

Northern California Service Centers  
Modesto | Hayward | Santa Rosa

800.640.1227 HotsyPacific.net

**hotsy**  
**PACIFIC**  
Nothing Cleans Like a Hotsy!