

Portable, self-contained, gas-engine, hot-water pressure washer is ideal for cleaning construction, mining and off-road vehicles.

MODEL
5645
Hot-Water
Pressure Washer

6 GPM @ 3000 PSI



■ **Pump slider** allows for easy belt maintenance and maximum performance.

■ **Upright, oil-fired burner** provides hot water to deliver exceptional cleaning performance.

■ **Simple, easy-to-use control panel** includes adjustable temperature control with precision safety controls. **Adjustable upstream dual detergent injection** ensures high-pressure sudsing for better cleaning.

■ **24 HP Honda V-Twin electric-start engine** powers this tough, off-road cleaning machine.

■ **Rust-proof, non-contaminating polyethylene 11-gallon fuel tanks** include fuel gauge in cap.

■ **Belt-drive operation** ensures a quieter-running machine. **Vibration isolators** absorb movement for a smoother-running machine.

■ **50-ft. high-pressure hose** for easy maneuverability around a large working area.

■ **8-gallon polyethylene float tank** maintains constant pressure and flow while preventing sediment from entering the machine's components.

■ **Hawk® triplex, belt-drive pump** carries seven-year crankcase and lifetime manifold warranties.

■ **Hawk® pre-set unloader valve** is remote mounted for less vibration.

■ **115V generator** creates electricity to run burner assembly and electrical outlet for low-wattage applications.

■ **Marine-style battery box** for protective enclosure.

■ **Heavy-duty trigger gun and wand** with insulated cool grips and quick-change nozzles.





Hotsy's Model 5645 provides robust cleaning power for contractors and cleaning professionals.

For tough cleaning on construction, mining and off-road vehicles, nothing comes close to the performance of a Model 5645. Employing its heavy-duty construction, the Model 5645 conquers even the most demanding cleaning jobs.

Model 5645 shown with optional portage kit.

Discover Hotsy's no-cost benefits

Choose the Model 5645 for its high performance and reliability. Then enjoy the benefits of doing business with the leader in industrial cleaning equipment. You'll find more than 120 models of pressure washers to choose from, free on-site demos, factory-trained service people, pre-delivery dealer prep, on-site machine check-out, operator training, local parts and accessory inventory and an unbeatable warranty program.

Accessories to match your application

Hotsy's custom accessories tailor the Model 5645 pressure washer to fit your specific requirements making your cleaning jobs faster, easier and more efficient. Choose from multiple-gun operation, extra hose lengths, hose reels, wand extensions, quick couplers, foam applicator, wet sandblaster, rotating brush and more.



Clean better with Hotsy detergents

Hotsy's broad selection of biodegradable detergents are formulated specifically for high-temperature, high-pressure cleaning. This means you get the best results from your Hotsy pressure washer while continuously protecting the machine. Exclusive advanced-formula Hotsy Continuous Clean (HCC) additives continuously clean the lime and mineral buildup that can occur in your washer's coil and fittings. This cleaning action reduces replacement costs and improves machine performance. Most Hotsy detergents are USDA and Canadian Agriculture approved. And they're concentrated, so a little goes a long way.



Call today for a demo!

Find out for yourself why the Hotsy Model 5645 is right for your cleaning jobs. Call your Hotsy distributor today for all the details and a FREE on-site demo.



Model 5645 Specifications

6 GPM @ 3000 PSI; 24 HP electric-start engine; oil-fired water heater; shipping weight: 1200 lbs.

Water Pump Volume:	6 GPM (22.7 lpm)/360 GPH (1362 lph)
Water Pump Pressure:	3000 PSI (207 bars)
Water Pump:	Hawk® triplex, positive-displacement pump; ceramic plungers, brass manifold, oil-bath crankcase.
Pump Drive:	24 HP gasoline engine, electric start. 11-gallon removable, polyethylene gas tank with fuel gauge in cap.
Oil-Fired Water Heater:	740,000 BTU/hr. UL-listed burner, pressure-atomizing type. Choice of #1 or #2 diesel fuel, kerosene or #1 home heating oil as fuel. Fuel filter standard, 11-gallon polyethylene fuel-oil tank. Fuel gauge in cap.
Heating Coil:	Schedule 80, ASTM A53 close coiling pipe; hydrostatic pressure tested; vertically fired. Heating coil is sheathed in a full-length sheet-metal wrap. Equipped with an independent welded heat-retention baffle plate.
Stack Size:	10" diameter.
Controls:	Adjustable temperature control, safety pressure relief-valve, pressure switch, on/off water-heater switch, dual detergent valve and automatic anti-rusting float valve.
Float Tank:	Removable, rust-proof polyethylene.
Wand Assembly:	Trigger-gun control with cool grip, quick coupled to a heavy-duty wand with insulated grip.
Nozzle:	Hardened stainless steel (0°, 15°, 40°)
Hose:	1/2" ID, 50 ft. wire braid, 3500 PSI working pressure; burst pressure is at least 4 times working pressure; oil and chemical resistant. Swivel fittings at both ends.
Portability:	Optional
Optional Accessories:	Multiple-gun operation, extra hose lengths, hose reels, wand extensions, quick couplers, downstream detergent injector, wet sandblaster, rotating brush and foam applicator.
Construction:	Heavy-gauge steel; angle-iron frame.
Finish:	High-gloss, powder coat.
Dimensions:	L-64" (162.6 cm); W-35" (88.9 cm); H-55" (139.7 cm)

Northern California Service Centers
Modesto | Hayward | Santa Rosa

800.640.1227 HotsyPacific.net

